



Nominal pipe size	Flange Brida				Hub cuello	Raised face Resalte	Drilling template Taladros			Approx. Weight Peso aprox.	
	D	J	b	h			m	g	Number		l
	Diámetro nominal	mm. inches	mm. inches	mm. inches			mm. inches	mm. inches	mm. inches	Número	mm. inches
1/2"	88,9 3 1/2	No counter Bore required in 150 Lb. THREADED FLANGES En las bridas THREADED 150 Lb, no se requiere ensanche de boca	11,1 7/16	47,6 1 7/8	30,2 1 3/16	34,9 1 3/8	4	15,9 5/8	60,3 2 3/8	0,9 2	
3/4"	98,4 3 7/8		12,7 1/2	52,4 2 1/16	38,1 1 1/2	42,9 1 11/16	4	15,9 5/8	69,8 2 3/4	0,9 2	
1"	107,9 4 1/4		14,3 9/16	55,6 2 3/16	49,2 1 15/16	50,8 2	4	15,9 5/8	79,4 3 1/8	1,4 3	
1 1/4"	117,5 4 5/8		15,9 5/8	57,1 2 1/4	58,7 2 5/16	63,5 2 1/2	4	15,9 5/8	88,9 3 1/2	1,4 3	
1 1/2"	127,0 5		17,5 11/16	61,9 2 7/16	65,1 2 9/16	73,0 2 7/8	4	15,9 5/8	98,4 3 7/8	1,8 4	
2"	152,4 6		19,1 3/4	63,5 2 1/2	77,8 3 1/16	92,1 3 5/8	4	19,05 3/4	120,6 4 3/4	2,7 6	
2 1/2"	177,8 7		22,2 7/8	69,8 2 3/4	90,5 3 9/16	104,8 4 1/8	4	19,05 3/4	139,7 5 1/2	3,6 8	
3"	190,5 7 1/2		23,8 15/16	69,8 2 3/4	107,9 4 1/4	127,0 5	4	19,05 3/4	152,4 6	4,5 10	
3 1/2"	215,9 8 1/2		23,8 15/16	71,4 2 13/16	122,2 4 13/16	139,7 5 5/12	8	19,05 3/4	177,8 7	5,4 12	
4"	228,6 9		23,8 15/16	76,2 3	134,9 5 5/16	157,2 6 3/16	8	19,05 3/4	190,5 7 1/2	6,8 15	
5"	254,0 10		23,8 15/16	88,9 3 1/2	163,5 6 7/16	185,7 7 5/16	8	22,2 7/8	215,9 8 1/2	8,6 19	
6"	279,4 11		25,4 1	88,9 3 1/2	192,1 7 9/16	215,9 8 1/2	8	22,2 7/8	241,3 9 1/2	10,9 24	
8"	342,9 13 1/2		28,6 1 1/8	101,6 4	246,1 9 11/16	269,9 10 5/8	8	22,2 7/8	298,4 11 3/4	17,7 39	
10"	406,4 16		30,2 1 3/16	101,6 4	304,8 12	323,8 12 3/4	12	25,4 1	361,9 14 1/4	23,6 52	
12"	482,6 19		31,8 1 1/4	114,3 4 1/2	365,1 14 3/8	381,0 15	12	25,4 1	431,8 17	36,3 80	
14"	533,4 21		34,9 1 3/8	127,0 5	400,0 15 3/4	412,7 16 1/4	12	28,6 1 1/8	476,2 18 3/4	50,0 110	
16"	596,9 23 1/2	36,5 1 7/16	127,0 5	457,2 18	469,9 16 1/4	16	28,6 1 1/8	539,7 21 1/4	64,0 140		
18"	635,0 25	39,7 1 9/16	139,7 5 1/2	504,8 19 7/8	533,4 21	16	31,7 1 1/4	577,8 22 3/4	68,0 150		
20"	698,5 27 1/2	42,9 1 11/16	144,5 5 11/16	558,8 22	584,2 23	20	31,7 1 1/4	635,0 25	81,6 180		
24"	812,8 32	47,6 1 7/8	152,4 6	663,6 26 1/8	692,1 27 1/4	20	34,9 1 3/8	749,3 29 1/2	118 260		